

Description	Prod.-No.	RB 35 SP RB 35 B Piccolo 35/50 X	RB 50 SP RB 50 X 40 RL-E	RB 80 X 60 RL-E	100 RL-E	Figure
HSS taper and deburring countersinks with Weldon shank • Ø 25 mm	18533	✓	✓ With Tool holder MK 2/3	✓ With Tool holder MK 2/3	✓ With Tool holder MK 2/3	
HSS taper and deburring countersinks with Weldon shank • Ø 30 mm	18536	✓	✓ With Tool holder MK 2/3	✓ With Tool holder MK 2/3	✓ With Tool holder MK 2/3	
HSS taper and deburring countersinks with Weldon shank • Ø 40 mm	18534	✓	✓ With Tool holder MK 2/3	✓ With Tool holder MK 2/3	✓ With Tool holder MK 2/3	
HSS taper and deburring countersinks with Weldon shank • Ø 55 mm	18537	-	-	✓	✓	
Coolant system for 40 RL-E, 60 RL-E, 100 RL-E, 130	18104	✓	✓	✓	✓	
Coolant system for RB 35 B	189311241	✓	-	-	-	
Coolant system for Piccolo 35/50 X, RB 35 SP, RB 50 SP, RB 50 X and 80 X, suitable for tool holder with internal cooling AMK-2 (Prod.-No. 18003) and AMK-3 (Prod.-No. 18025)	189412029	-	✓	✓	-	
Coolant pressure bottle 0.5 l suitable for Rotabest® V32	18103	✓	✓	✓	✓	
ALFRA 2000 Cutting and drilling spray 405 ml can	21010	✓	✓	✓	✓	
ALFRA 4000 High performance cutting oil spray 300 ml can	21040	✓	✓	✓	✓	
High performance wax stick. Ideal for core drill boreholes on the wall or ceiling (overhead drilling), as paste adheres to the cutting edge.	09012	✓	✓	✓	✓	