





### **MIG 200i**

Rated Input Voltage	240
Phase/Frequency	1Ph/50-60Hz
Rated Input Current	26.5
Output Current Range	50-200A
Output Voltage Range	16.5-24
Duty Cycle	30
Power Factor	0.73
Efficiency	80
Wire Feeding Speed	2-15
Post Flow	1.0±0.5
Wire Diameter	0.6/0.8/1.0
Insulation Grade	F
Protection Grade	IP215
Welding Thickness	above 0.8



### **MMA 1600**

Rated Input Voltage	240
Phase/Frequency	1Ph/50-60Hz
Rated Input Power	6.5KVA
Rated Duty Cycle	60%
Output Amperage Range	20-160A
Output Voltage Range	20.8-26.4V
Output No-load Voltage	62V
Efficiency	85%
Power Factor	0.76
Protection Grade	IP23
Insulation Class	F
Net Weight	6Kg
Dimensions	29*12*20CM



**WELD**  
WIDER RANG. EASIER FEED.

### **MMA 2000**

Rated Input Voltage	240
Phase/Frequency	1Ph/50-60Hz
Rated Input Power	8.7KVA
Rated Duty Cycle	60%
Output Amperage Range	20-200A
Output Voltage Range	20.8-28.4V
Output No-load Voltage	62V
Efficiency	85%
Power Factor	0.76
Protection Grade	IP23
Insulation Class	F
Net Weight	10Kg
Dimensions	29*12*20CM



### **TIG 200**

Rated Input Voltage	240
Phase/Frequency	1Ph/50-60Hz
Rated Input Power	5.6KVA   6.5KVA
Rated Input Current	25.3A   29.7A
Rated Duty Cycle	45%
Output Amperage Range	10-200A   20-160A
Current Adjustment Range	10-200A   20-160A
Output No-Load Voltage	56V
Initiation Mode	HF
Efficiency	85%
Post Flow Time	0-10S
Power Factor	0.76
Protection Grade	IP 23
Insulation Class	F
Net Weight	10KG
Dimension	35*15*23CM

### **MMA 2500**

Rated Input Voltage	240
Phase/Frequency	1Ph/50-60Hz
Rated Input Power	11.6KVA
Rated Duty Cycle	60%
Output Amperage Range	40-250A
Output Voltage Range	21.6-30V
Output No-load Voltage	62V
Efficiency	85%
Power Factor	0.76
Protection Grade	IP23
Insulation Class	F
Net Weight	15Kg
Dimensions	37.5*16*26CM

